

Heavy Duty Series



64 HD
Oil-filled



X64 HD
Air-filled

64 HD and X64 HD, 25-60 BHP
Horizontal Flanged Discharge 1725 RPM

ZOELLER 
ENGINEERED PRODUCTS

TRUSTED. TESTED. TOUGH.®

zoellerengineered.com

64 HD and X64 HD

25-60 BHP

Horizontal Flanged Discharge 1725 RPM

FEATURES*

- 230 & 460 Volt 3 Phase
- 4" or 6" Horizontal discharge
- 3-1/8" or 4" spherical solids capability
- Enclosed impeller
- 1725 RPM
- Durable, epoxy coated cast iron construction
- Oil filled motor (non-explosion proof), air filled motor (explosion proof)
- Dual mechanical shaft seals carbon/ceramic
- Buna-N elastomers
- Thermal sensor and moisture detection
- 304 Stainless steel hardware
- 100% Computerized water tested

OPTIONS*

- Seal upgrades
- Additional cord lengths
- Viton elastomers
- Trimmed, vortex or bronze impeller
- Certified performance audits
- Explosion proof motor

APPLICATIONS:

- Pumping stations
- Storm water removal
- Wastewater transfer
- Commercial wastewater solids handling

*consult tech data sheet for specific technical information

Tech Data Sheets	
64 HD	ZM2968
X64 HD	ZM2970